



SPECIFICATIONS

- 1. Current Rate : 3AMP
- 2. Operation Temperature: -40°C to +105°C
- 3. Contact Resistance : 20m Ω Max.
- 4. Insulation Resistance: 1000M Ω Min.
- 5. Withstanding Voltage : AC 1000V
- 6. Insulator Material : Polyester (UL94V-0) Standard: PBT
- 7. Contact Material : Brass
- 8. Contact plating : Au or Sn over 50μ" Ni

| No. of Contacts | A | B | C |
|--------------------|--------|-------|-------|
| 10 | 32.00 | 21.84 | 10.16 |
| 14 | 37.08 | 26.92 | 15.24 |
| 16 | 39.62 | 29.46 | 17.78 |
| 20 | 44.70 | 34.54 | 22.86 |
| 26 | 52.32 | 42.16 | 30.48 |
| 30 | 57.40 | 47.24 | 35.56 |
| 34 | 62.48 | 52.32 | 40.64 |
| 40 | 70.10 | 59.94 | 48.26 |
| 50 | 82.80 | 72.46 | 60.96 |
| 60 | 95.50 | 85.34 | 73.66 |
| 64 | 100.58 | 90.42 | 78.74 |



深圳市鑫南天科技有限公司
Shenzhen XinNanTian Technology Co., Ltd

| | | | |
|------------------------------|-----------|------------|-------|
| DIMENSIONS INT: mm | | DRAWINGS: | |
| UNLESS OTHERWISE SPECIFIABLE | | COCO | |
| DIMENSION | TOLERANCE | DATE: | DATE: |
| X.X: ± | 0.38 | 2014/01/15 | |
| X.XX: ± | 0.25 | 2014/01/15 | |
| X.XXX: ± | 0.10 | 2014/01/15 | |
| ANGULAR: ± | 1° | | |

| | | | | |
|--------------|---------|-------------|------|------|
| REVISION NO. | EGR NO. | DESCRIPTION | MARK | DATE |
| 1 | | | | |
| 2 | | | | |